



## CNC-3335-MS – 2MP WDR Motorized SMART IP Bullet



### Features

- **2 Megapixel** 1920x1080 @25fps
- **H.265+** Compression
- **2.8~12mm Motorized** Zoom Lens
- **Auto Focus**
- **120dB True WDR**
- 3D-DNR, DSS, BLC, HLC, Defog, ROI
- LED Array, 0 Lux up to 50m
- **Audio** In/Out, **Alarm** In/Out, CVBs
- POE / 12VDC Dual Power
- Support **μSD** up to 128GB
- Smart Functions : **Object Removal, Line Crossing, Region Intrusion, People Counting, Crowd Density, Face Capture, Flow Counting**

### SPECIFICATION



Model	CNC-3335-MS
Image Sensor	1/2.8" progressive scan CMOS Sensor
Resolution	1920x1080 @25fps (PAL)
Shuttle	1/25s ~ 1/100,000s
Lens	M14 2.8-12mm Motorized Zoom Auto Focus
Viewing Angle	103°~32° Horizontal
LEDs	IR LED Array 50~70m Distance
Day & Night	Filter Change or TDN (True Day & Night)
Video Compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Audio Compression	G711A/U
Network	10/100-BaseT, RJ45
Bit Rate	64Kbps ~ 6Mbps
Working Environment	-30° ~ +60°C, <90° Humidity (Non-Condensing)
Power	POE IEEE 802.3af compliant/12VDC, Max. 12W
Dimension	279.5 x 100.3 x 88.9mm, 1.04kg